

## Equipo - WY-100



Compacto y versátil, el Nakamura Tome WY-100 cuenta con dos torretas, superior e inferior, tiene dos husillos izquierdo y derecho; las torretas cuentan con 12 posiciones, indexando media posición, permitiendo de 24 hasta 48 herramientas de torneado por torreta. Es ideal para el mecanizado eficiente de piezas pequeñas, ofreciendo capacidades avanzadas y resultados precisos.

Incluye:

- Nuevo control NT Smart X.
- Pantalla touch.
- Airbag.
- NT Working navigator.
- y más.

### WY-100

Capacity	?42mm / ?51mm / ?65mm
Max. turning diameter	175mm / 200mm
Max. turning length	588mm / 570mm
Distance between centers	max.820mm/min.200mm
Bar capacity	42mm / 51mm / 65mm
Chuck size	165mm(6?)
Axis travel	
Slide travel X1/X2	135mm / 150mm/141mm
Slide travel Z1/Z2	588mm/578mm / 570mm/560mm
Slide travel Y1/Y2	±31mm / ±32.5mm
Left and right spindle	
Spindle speed	6,000min-1 / 5,000min-1 / 4,500min-1
spindle drive motor L/R	11/7.5kW
spindle drive motor L/R	75.4/38.6N?m / 77/39.4N?m / 80.9/41.4N?m
Upper turrets	
Number of turrets	1
Spindle speed	6,000min-1
Driven motor power and torque	7.1/2.2kW ???16N.m
Type of turret head	Dodecagonal
Number of index positions	24
Rotary system	Individual rotation
Number of driven-tool stations	12
Lower turrets	
Number of turrets	1
Spindle speed	6,000min-1
Driven motor power and torque	7.1/2.2kW max. 16N.m
> Type of turret head	Dodecagonal
Number of index positions	24
Rotary system	Individual rotation

**Obtén asesoría personalizada: Llámamos: 55 4125 9100 WhatsApp: (+52) 55 8044 4474**

## General

### Floor space

H	2,395mm
L	2,780mm
W	2,070.5mm
Machine weight	7,400kg